PATENT ABSTRACTS OF JAPAN

(11)Publication number:

11-251687

(43)Date of publication of application: 17.09.1999

(51)Int.CI.

H01S 3/18 H01L 33/00

(21)Application number: 10-054634

(71)Applicant:

MATSUSHITA ELECTRIC IND CO LTD

(22)Date of filing:

06.03.1998

(72)Inventor:

HASEGAWA YOSHITERU


ISHIBASHI AKIHIKO **TSUJIMURA AYUMI** KIDOGUCHI ISAO **MIYANAGA RYOKO** KAMIYAMA SATOSHI **KUME MASAHIRO BAN YUZABURO**


(54) MANUFACTURE OF SEMICONDUCTOR AND SEMICONDUCTOR DEVICE

(57)Abstract:

PROBLEM TO BE SOLVED: To form a p-n junction having a steep dopant profile in a gallium nitride semiconductor.

SOLUTION: On a sapphire substrate 10, an n-type GaN contact layer 12, an n-type Al0.1Ga0.9N clad layer 13, a first GaN light guide layer 14, an In0.20Ga. 0.80N quantum well active layer 15, and a second GaN light guide layer 16 are successively formed. On the upper surface of the second light guide layer 16, an Al0.1Ga0.9N diffusion suppressing layer 17 having a film thickness of 20 nm and doped with Mg as a p-type dopant and Si as an n-type dopant is formed and, on the upper surface of the layer 17, a p-type A0.1Ga0.9N clad layer 18 is formed.





LEGAL STATUS

[Date of request for examination]

23.05.2000

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

3408413

[Date of registration]

14.03.2003

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office